

**FEATURES :**

- \* Simple & Quick 4 Keys
- \* Small Size
- \* Digital Calibration
- \* 2 Set Points
- \* RS232 & 4-20 mA Output
- \* External Tare
- \* Panel Mountable
- \* Peak Hold Facility

**SPECIFICATIONS :**

Circuitry	:	Microprocessor Based.
Resolution	:	0 – 20000 Counts.
Display	:	6 Digit 0.56" Seven Segment LED.
Accuracy	:	$\pm 0.1\% \pm 1$ Count.
Thermal Drift	:	$< 100$ ppm/ $^{\circ}$ C.
Excitation Voltage	:	5 V DC.
Power Supply	:	230 V, 50 Hz AC Mains.
Relays	:	2 Nos. 5A, 230 V/50 Hz, Resistive Load.
Operating Temperature	:	0 $^{\circ}$ C to 50 $^{\circ}$ C.
Analog Output	:	4 - 20 mA (upto 150 Ohms Load).
PC Connectivity	:	RS-232C.
Minimum Bridge Resistance	:	85 $\Omega$ (4 off 350 $\Omega$ Sensors in Parallel).
Dimensions	:	48 x 96 x 130 mm Deep.
Panel Cutout Dimensions	:	46 x 90 mm.