## **FEATURES:**

- Simple & Quick 2 or 4 Buttons
- Small Size & Portable
- **Battery Operated**
- **Digital Calibration**
- **Peak Hold Facility**
- **Backlit Facility**



## **SPECIFICATIONS:**

Circuitry Microprocessor Based.

0 - 99999 Counts. Resolution Display 5 Digits 20 mm LCD. ± 0.1% ± 1 Count. **Accuracy Excitation Voltage** 2.5 V DC (± 1%).

**Power Supply** 3.6 V Battery / 9 V DC Adapter.

**Operating Temperature** 0° C to 50° C. Enclosure ABS Plastic.

**Dimensions** 100 x 190 x 45 mm (approx).

Weight 75 gms. (approx).

F#1, Paradise Apartments, No. 11, 1<sup>st</sup> Floor, 5<sup>th</sup> Cross, Prashanthnagar, Bangalore - 560 079. Office Ph: 080 - 2348 1364, 6576 1259. Fax: 080 - 2328 3728. E-mail: sales@epochloadcell.com.

No. 16, Bhadrappa Estate, 54, Magadi Main Road, Kamakshipalya, Bangalore - 560 079. Factory:

Ph: 080 - 2328 7998. E-mail: epochinstruments@yahoo.com, Web: www.epochloadcell.com.