

DIGITAL INDICATOR

SPECIAL FEATURES :

- ⇒ Simple & Quick 4 Buttons
- ⇒ Small Size
- ⇒ 5 Set Points
- ⇒ Digital Calibration
- ⇒ 100 Samples/Sec
- ⇒ RS 232 & 4-20 mA Output
- ⇒ Panel Mountable
- ⇒ Peak Hold Facility



SPECIFICATIONS :

Model	:	SM – 15 – A.
Resolution	:	0 – 19999 Counts.
Display	:	6 Digit Red 0.56" Seven Segment LED.
Accuracy	:	± 0.1% ± 1 Count.
Thermal Drift	:	< 100 ppm/°C.
Excitation Voltage	:	5 V DC.
Power Supply	:	230 V, 50 Hz AC Mains.
Update Rate	:	Variable from 4 Samples/Sec to 100 Samples/Sec.
Circuitry	:	Microprocessor Based.
Relays	:	5 Nos. 5A, 230 V/50 Hz, Resistive Load.
Analog Output	:	4 – 20 mA (Max load 300 Ohms).
Operating Temperature	:	0° C to 50° C.
Enclosure	:	ABS Plastic Case.
Minimum Bridge Resistance	:	85 Ω (4 off 350 Ω Sensors in Parallel).
Dimensions	:	96 x 96 x 130 mm Deep.

Please Communicate to :

EPOCH

Instruments & Controls Pvt. Ltd.

Office : MIG 132, 2nd Stage, 80 Feet Road, K.H.B. Colony, Basaveshwaranagar, Bangalore – 560 079.

☎ : 080 – 2348 1364, 6576 1259. ☎ : 080 – 2328 3728. E-mail : epochic@dataone.in.

Factory : No. 16, Bhadrappa Estate, 54, Magadi Main Road, Kamakshipalya, Bangalore – 560 079. ☎ : 080-2328 7998.

Branch : No. 403, Kemp Plaza, B-Wing, Opp. Mind Space, Chincholi Bunder, Malad (West), Mumbai – 400 064.

☎ : 022 – 4003 0704, 4003 0705, 4003 0706. ☎ : 022 – 4003 0707. E-mail : synopsis@vsnl.com.