

WEB TENSION LOAD CELL

SPECIAL FEATURES

- ✎ *Easy to Install*
- ✎ *Good Reliability*
- ✎ *Temperature Compensated*



SPECIFICATION

Model	:	LWT - 11, 21, 51, 12.
Rated Load Capacity	:	10, 20, 50, 100 Kgs.
Rated Output Sensitivity	:	1 mV/V \pm 0.25 %.
Input Resistance	:	350 \pm 10 Ohms.
Output Resistance	:	350 \pm 3 Ohms.
Excitation Voltage	:	10 to 12 Volts DC/AC (RMS).
Non Linearity	:	\pm 0.50 % of Rated Output.
Hysteresis	:	\pm 0.50 % of Rated Output.
Non Repeatability	:	\pm 0.10 % of Rated Output.
Zero Balance	:	2 % of Rated Output.
Operatable Temperature Range	:	0° C to 65° C.
Storage Temperature Range	:	- 20° C to 85° C.
Temperature Effect on Zero	:	0.005 % of Rated Output/°C.
Temperature Effect on Output	:	0.010 % of Rated Output/°C.
Over Load Rating, Safe	:	150 % of Rated Capacity.
Over Load Rating (Ultimate)	:	200 % of Rated Capacity.