

**FEATURES :**

- \* *Simple & Quick 4 Keys*
- \* *Small Size*
- \* *Digital Calibration*
- \* *2 Set Points*
- \* *External Tare*
- \* *Panel Mountable*
- \* *Peak Hold Facility*

**SPECIFICATIONS :**

Circuitry	:	Microprocessor Based.
Resolution	:	0 – 20000 Counts.
Display	:	6 Digit 0.56" Seven Segment LED.
Accuracy	:	$\pm 0.1\% \pm 1$ Count.
Thermal Drift	:	< 100 ppm/°C.
Excitation Voltage	:	5 V DC.
Power Supply	:	230 V, 50 Hz AC Mains.
Relays	:	2 Nos. 5A, 230 V/50 Hz, Resistive Load.
Operating Temperature	:	0° C to 50° C.
Minimum Bridge Resistance	:	85 $\Omega$ (4 off 350 $\Omega$ Sensors in Parallel).
Dimensions	:	48 x 96 x 130 mm Deep.
Panel Cutout Dimensions	:	46 x 90 mm.

**Office** : F # 1, Paradise Apartments, No. 11, 1<sup>st</sup> Floor, 5<sup>th</sup> Cross, Prashanthnagar, Bangalore - 560 079.  
Ph : 080 - 2348 1364, 6576 1259. Fax : 080 - 2328 3728. E-mail : sales@epochloadcell.com.

**Factory** : No. 16, Bhadrappa Estate, 54, Magadi Main Road, Kamakshipalya, Bangalore - 560 079.  
Ph : 080 - 2328 7998. E-mail : epochinstruments@yahoo.com, Web : www.epochloadcell.com.