

FEATURES :

- * *Simple & Quick 6 Buttons*
- * *Small Size & Portable*
- * *Battery Operated*
- * *Digital Calibration*
- * *100 Samples/Sec*
- * *RS 232 Output*
- * *Peak Hold Facility*
- * *100 Data Storage*
- * *Backlit Facility*
- * *mV Check Facility from Load Cell*

SM-13-F**SPECIFICATIONS :**

Circuitry	:	Microprocessor Based.
Resolution	:	0 – 99999 Counts.
Display	:	5 Digits 18 mm LCD.
Accuracy	:	$\pm 0.1\% \pm 1$ Count.
Thermal Drift	:	< 100 ppm/ $^{\circ}$ C.
Excitation Voltage	:	5 V DC ($\pm 1\%$).
Power Supply	:	6 V Battery / 9 V DC Adapter.
Operating Temperature	:	0 $^{\circ}$ C to 50 $^{\circ}$ C.
PC Connectivity	:	RS-232C.
Enclosure	:	ABS Plastic.
Dimensions	:	250 x 135 x 45 mm (approx).

Office : F # 1, Paradise Apartments, No. 11, 1st Floor, 5th Cross, Prashanthnagar, Bangalore - 560 079.
Ph : 080 - 2348 1364, 6576 1259. Fax : 080 - 2328 3728. E-mail : sales@epochloadcell.com.

Factory : No. 16, Bhadrappa Estate, 54, Magadi Main Road, Kamakshipalya, Bangalore - 560 079.
Ph : 080 - 2328 7998. E-mail : epochinstruments@yahoo.com, Web : www.epochloadcell.com.