

**WL-12****FEATURES :**

- \* *Wireless up to 50 Mtrs.*
- \* *Simple & Quick 5 Keys*
- \* *1 inch LED Display*
- \* *Digital Calibration*
- \* *Panel Mountable*
- \* *Peak Hold Facility*

**SPECIFICATIONS :**

Circuitry	:	Microprocessor Based.
Resolution	:	0 – 20000 Counts.
Display	:	6 Digit 1" Seven Segment LED.
Accuracy	:	$\pm 0.1\% \pm 1$ Count.
Thermal Drift	:	$< 100$ ppm/ $^{\circ}$ C.
Power Supply	:	230 V, 50 Hz AC Mains.
Operating Temperature	:	$0^{\circ}$ C to $50^{\circ}$ C.
No. of Load Cells Support	:	4 Nos. of 350 $\Omega$ Load Cells in Parallel.
Wireless Distance	:	Up to 50 Mtrs. Line of Sight.
Dimensions	:	96 x 192 x 150 mm Deep.

**Office** : F # 1, Paradise Apartments, No. 11, 1<sup>st</sup> Floor, 5<sup>th</sup> Cross, Prashanthnagar, Bangalore - 560 079.  
Ph : 080 - 2348 1364, 6576 1259. Fax : 080 - 2328 3728. E-mail : sales@epochloadcell.com.

**Factory** : No. 16, Bhadrappa Estate, 54, Magadi Main Road, Kamakshipalya, Bangalore - 560 079.  
Ph : 080 - 2328 7998. E-mail : epochinstruments@yahoo.com, Web : www.epochloadcell.com.